

LPT Through Bore - Standard





Features

- Transmit analog and digital signal
- The power and signal are mixed transmitted, and the signal categories are as follows:
- Ethernet: Rate (10Mbps/100Mbps/1000Mbps)
- Industrial Ethernet: EtherNet , EtherCAT ,ProPNet, Powerlink, SercosIII/IP, etc.
- ⊚HD video: SDI, LVDS, etc.
- Serial communication: RS232, RS485, RS422, etc.
- Ouniversal Serial Bus: USB2.0
- ⊚Industrial Fieldbus: CANBus, ProPBus, InterBus, CC-Link, DeviceNet, etc.
- Sensor signal: thermal resistance, thermocouple, strain gauge, etc.
- Long service life, maintenance-free
- ©Easy to install



Technical specification parameters

Electrical & Electronics		Me	echanical	Environmental	
Number of	06/12/18/24	Rotating Speed	0~300rpm	Temperature	Industrial: -20°C~+60°C
Circuits					Military: -55°C~+80°C
Current	5A(Signal)/10A/15A	Contact Material	The inclineering plastic in Hilmigity		95%,100%RH or higher
Voltage	380VAC/DC	Housing Material	Aluminum	Protection Grade	IP50
Dielectric Strength	1000VAC@50Hz	Torque	≤0.1N.m/6 circuits, +0.03N.m/6 circuits	Others	
Insulation Resistance	≥500MΩ@500VDC	Wire Type	Teflon or others	Life Span	10 million (customizable)
Dynamic Contact Resistance	Min 1mΩ	Wire Length	rotor/stator: 300mm	пе зрап	



Selection table

LPT Standard Through-bore Slip Rings

Model	ID (mm)	OD (mm)	Voltage	Current	Circuits	Rotating Speed (rpm)
LPT012	φ12.7	φ53		5A/Signal	6~24	300
		'	240VAC/DC	5A/Signal		
		φ56		10A		
LPT025	φ25.4	φ86	240VAC/DC 380VAC/DC	5A/Signal	6~24	300
				10A		
				15A		
LPT038	φ38.1	φ99	240VAC/DC 380VAC/DC	5A/Signal	6~24	300
				- 10A		
				15A		
LPT050		φ119	240VAC/DC	5A/Signal	6~24	300
	φ50			10A		
				15A		
LPT060	φ60	φ135	240VAC/DC	5A/Signal	6~24	300
				10A		
				15A		
LPT070	φ70	φ135	240VAC/DC	5A/Signal	6~24	300
				10A		
				15A		
LPT080	φ80	φ160	240VAC/DC	5A/Signal	6~24	300
				10A		
				15A		
LPT096	φ96	φ185	240VAC/DC	5A/Signal	6~24	300
				10A		
				15A		
LPT120	φ120	φ207	240VAC/DC	5A/Signal	6~24	300
				10A		
				15A		
LPT150	φ150	φ250	240VAC/DC	5A/Signal	6~24	300
				10A		
				15A		
LPT180	φ180	φ298	240VAC/DC	5A/Signal	6~24	300
				10A		
				15A		

[•] The standard LPT models support the following signal types: serial communication, RTD signals, thermocouple signals, sensor signals, and encoder signals.

[•] Note: For additional signal transmission types, such as Ethernet, USB, HDMI, DP, SDI, GMSL, CameraLink, MIPI, LVDS, analog HD video signals, and Þeldbus, please contact us.



Model Description

LPX XXX- XXXX-XXX-XX - X X

- Combination type:
- FO for Fiber Optic
- A for Air Over,
- L for Liquid Over,
- G for Oil Over
- is the number of paths of the combined rotary couplings
- Same signals are counted together,
 different signals are listed in wiring order;
 special signals (e.g. USB, Ethernet, IF) are listed at the end.
 U1/U2/U3: represent USB1.0 / 2.0 / 3.0 respectively
 E1/E2/E3: represent 10M / 1000M / 1000M Ethernet respectively
 MF: represent IF signal (above 30MHz)
 Other signals are uniPed with S.
- Number of rings and current, number of rings with the same current, if there are several groups with different currents, arranged by current from largest to smallest
- For through-hole or half-through-hole sizes,

always round to the nearest whole number, or "000" for solids.

PT: Standard Hollow Shaft Slip Rings / LPTS: Hollow Shaft Slip Rings for Heavy Machinery

LPK: Integral Disk Slip Rings / LPKS: Separate Disk Slip Rings / LPS: Split Disk Slip Rings


LPA: High Current Slip Rings / LPW: Wind Power Slip Rings

Product Selection Example Description

- Example 1: LPT025-0615-02U2
 - → Hollow shaft slip ring, 25mm overbore, 6-way 15A current, 2 sets of USB2.0 signals
- Example 2: LPT000-0210-02E2FS-01A
 - → Electrical combination hollow shaft slip ring, solid shaft (no bore), 2-way 10A current, 2 sets of 100Mbps Ethernet signals, with Waterproof (up to IP65), 1 channel over air



Product Dimension Drawing



Rotating interface: The point where the rotating part meets the stationary part.

Customization options

Note: The following special requirements can be customized, JINPAT most of the basic accessories are standardized, modular, non-standard customization can also greatly reduce the cost and delivery time.

- 1. Customized rotor and stator outlet and outlet length
- 2. Due to structural limitations, can be customized in accordance with the speciPed length or height or external diameter
- 3 Yasukawa, Panasonic, Siemens and other servo system signals, power lines, and encoder lines mixed slip ring
- **4.** Mixed high-speed data transmission (including Ethernet, USB, RS232, RS485, Profbus, CanBUS, CANOPEN, DeviceNET, CANBUS, CANPUS). CANOPEN, DeviceNET, CC-LINK, ProPNET, EtherCAT and other types of industrial lines).
- **5**. Anti-shock, high temperature and other special environment customization
- 6. Can be mixed with pneumatic, hydraulic rotary joints integrated pneumatic-electrical-hydraulic slip ring
- 7. Military grade
- 8. Waterproof, underwater mode optional, IP65,IP68 optional